TEMPORARY CHAIN LINK FENCE



Anti-Corrosion & Visible Temp Chain Link Fencing

Temporary fencing with chain link mesh infill, which a major exporting portable fencing to Australia, America, England and Africa market. It is modular and plug-in installation for quick and efficient set up and take down when quickly established barriers are needed.



FEATURES & BENEFITS

Hand Craft Technology

Workers use galvanized wire wrapped the chain link mesh with steel frame together by tension bars and tension bands in a rather tension way.



Stable Fence Frame

360° full welding by hand and hot dipped galvanized surface treatment to prevent cracks and corrosion.



Quick Installation

No need to dig holes or laying foundations, just connect the panel and the feet with a pre-designed plug-in way.




Adaptable

Three types of stable fence feet available can find the best anchor point, even uneven ground, sloping sites.



TECHNICAL DETAILS



6' × 8' Temp Chain Link Fencing

Dimensions (H \times L): $6' \times 8'$.

Frame O.D.: 1.25", 1.5", 1.6" round optional.

Brace: Cross, vertical, horizontal brace with 1" round or the

same with frame O.D.

Wire diameter: 9, 10.5, 11, 11.5, 12 gauge optional.

Mesh opening: 2", 2.25", 2.4", 2.75" optional.

Finish: Hot dipped galvanized & Pre-galvanized.










TECHNICAL DETAILS



6' × 10' Temp Chain Link Fencing

Dimensions (H \times L): $6' \times 10'$.

Frame O.D.: 1.25", 1.5", 1.6" round optional.


Brace: Cross, vertical, horizontal brace with 1" round or the

same with frame O.D.

Wire diameter: 9, 10.5, 11, 11.5, 12 gauge optional.

Mesh opening: 2", 2.25", 2.4", 2.75" optional.

Finish: Hot dipped galvanized & Pre-galvanized.



6' × 12' Temp Chain Link Fencing

Dimensions (H \times L): 6' \times 12'.

Frame O.D.: 1.25", 1.5", 1.6" round optional.

Brace: Cross, vertical, horizontal brace with 1" round or the

same with frame O.D.

Wire diameter: 9, 10.5, 11, 11.5, 12 gauge optional.

Mesh opening: 2", 2.25", 2.4", 2.75" optional.

Finish: Hot dipped galvanized & Pre-galvanized.



6' × 14' Temp Chain Link Fencing

Dimensions (H \times L): $6' \times 14'$.

Frame O.D.: 1.25", 1.5", 1.6" round optional.


Brace: Cross, vertical, horizontal brace with 1" round or the

same with frame O.D.

Wire diameter: 9, 10.5, 11, 11.5, 12 gauge optional.

Mesh opening: 2", 2.25", 2.4", 2.75" optional.

Finish: Hot dipped galvanized & Pre-galvanized.



8' × 10' Temp Chain Link Fencing

Dimensions (H × L): $8' \times 10'$.

Frame O.D.: 1.25", 1.5", 1.6" round optional.

Brace: Cross, vertical, horizontal brace with 1" round or the

same with frame O.D.


Wire diameter: 9, 10.5, 11, 11.5, 12 gauge optional.

Mesh opening: 2", 2.25", 2.4", 2.75" optional.

Finish: Hot dipped galvanized & Pre-galvanized.



TECHNICAL DETAILS



8' × 12' Temp Chain Link Fencing

Dimensions (H \times L): 8' \times 12'.

Frame O.D.: 1.25", 1.5", 1.6" round optional.

Brace: Cross, vertical, horizontal brace with 1" round or the


same with frame O.D.

Wire diameter: 9, 10.5, 11, 11.5, 12 gauge optional.

Mesh opening: 2", 2.25", 2.4", 2.75" optional.

Finish: Hot dipped galvanized & Pre-galvanized.

ACCOCIATED ACCESSORIES



Square/Oval fence feet

Dimensions ($H \times W \times TH$):

36" × 13.75" × 20",

 $30" \times 18" \times 20"$ optional.



Flat fence feet

Dimensions ($H \times W \times TH$):

 $23.6" \times 4.3" \times 0.3"$

 $35.4" \times 3.0" \times 0.25"$ optional.

Hole size O.D.: 19 mm.

Interior round steel rod/pipe: 30 mm O.D. × 150 mm H.

Exterior square steel rod/pipe: $30 \times 30 \times 150$ mm.

Rod space: 30 mm.



Clamp

Clamp center distance: 80, 90, 100 mm optional.

Applied post O.D.: 25, 28, 32, 38, 40, 42 mm optional.

Accessory List: 2 pieces clamps with 1 bolt and 1 nut.

Finish: Hot dipped galvanized & Pre-galvanized.